Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-529-5639

view Online at https://aerobasegroup.com/hsi//4/20-01-529-5659	
Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.500 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit $% \left(1,1,2,2,3,3,3,3,3,3,3,3,3,3,3,3,3,3,3,3,$	
Outside Diameter:	
0.810 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Black	
End Application:	
Forward propulsion system	
Connection Style:	
Swivel nut, gasket seal 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Thready Qty Per Inch (tpi):	
16 1st end	
Burst Test Pressure:	
16000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided synthetic cord and outer layer molded polyurethane	
Maximum Operating Pressure:	
4000.0 pounds per square inch	
Thread Size:	
0.812 inches 1st end	
Flow Angle:	
90.0 degrees 1st end	
Outer Covering Environmental Protection:	
Abrasion resistant	
Criticality Code Justification:	
Feat	
Inside Surface Condition:	
Smooth	
Onooth	

AeroBase Group

Measuring Method And Length:

43.500 inches working

Product Name:

Transmiss hose 1

Special Features:

Critical technology, export control; stainless steel fittings, polymeric core, aramid layer, urethane cover; length to be determined at installation

Media For Which Designed:

Air and hydraulic fluid single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0