NSN 4720-01-529-5653

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-529-5653

00
Cross Sectional Shape:
Round Thread Class
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.810 inches
Minimum Inside Bending Radius:
4.000 inches
Exterior Color:
Black
End Application:
Forward propulsion system
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and outer layer molded polyurethane
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.812 inches 1st end
Outer Covering Environmental Protection:
Abrasion resistant
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth
Measuring Method And Length:
a.a.aga.a.a.a.a.a.a.g

0.001 inches

NSN 4720-01-529-5653

Product Name:

Nonmetallic Hose Assembly - Page 2 of 2



Transmiss hose 2					
Special Features:					
Critical technology, export control	ol; stainless steel fittings,	, polymeric core,	aramid layer,	urethane cover;	length to be determined at
installation					
Media For Which Designed:					
Air and hydraulic fluid single res	ponse				
Thread Series Designator:					
Un 1st end					
Shelf Life:					
N/a					
Unit Of Measure:					
Demilitarization:					
No					
Fiig:					
A542a0					