Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-529-8535

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Outside Diameter: |
| 0.890 inches |
| Minimum Inside Bending Radius: |
| 3.500 inches |
| Exterior Color: |
| Black |
| End Application: |
| Forward propulsion section assembly, rmv |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external tube 1st end |
| Thready Qty Per Inch (tpi): |
| 16 1st end |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fiber and outer layer polyester |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Thread Size: |
| 0.812 inches 1st end |
| Inside Surface Condition: |
| Smooth |
| Media For Which Designed: |
| Air and hydraulic fluid single response |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4720-01-529-8535

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

