Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-530-4934

| Cross Sectional Shape: | |
|---|--|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.602 inches | |
| Tempurature Rating: | |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.750 inches | |
| Minimum Inside Bending Radius: | |
| 1.500 inches | |
| Connection Style: | |
| Swivel nut flare 2nd end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Burst Test Pressure: | |
| 16000.0 pounds per square inch | |
| Maximum Operating Pressure: | |
| 3000.0 pounds per square inch | |
| Thread Size: | |
| 0.438 inches 1st end | |
| Seat Angle: | |
| 37.0 degrees 2nd end | |
| Flow Angle: | |
| 90.0 degrees 2nd end | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 67.000 inches working | |
| Thread Series Designator: | |
| Unjf 1st end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| | |

NSN 4720-01-530-4934

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

