

View Online at <https://aerobasegroup.com/nsn/4720-01-530-5407>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.440 inches

**Minimum Inside Bending Radius:**

1.750 inches

**Exterior Color:**

Olive drab

**End Application:**

Fwd fuelsalge

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

200.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and outer layer braided cotton cord

**Maximum Operating Pressure:**

50.0 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

100.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

7.000 inches

**Product Name:**

Hose assembly, nonmetallic-low pressure, fitting end to elboe 90, flared tube

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A542a0