Nonmetallic Tubing Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-531-4281

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.275 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
1.125 inches
Exterior Color:
Black
End Application:
Electrical equipment group
Connection Style:
Flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Features Provided:
Identical ends
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
1250.0 pounds per square inch
Maximum Operating Pressure:
312.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
625.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and salt water resistant
Inside Surface Condition:
Smooth

Nonmetallic Tubing Assembly - Page 2 of 2



Measuring Method And Length:

48.000 inches

Special Features:

4720-01-095-2040 hose, 4730-00-139-3885 fittings, assembled with markings and marker cable; pneumatic

Material:

Plastic polyamide tube

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A541y0