## NSN 4720-01-531-4281

Nonmetallic Tubing Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-531-4281
Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.275 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
1.125 inches
Exterior Color:
Black
End Application:
Electrical equipment group
Connection Style:
Flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Features Provided:
Identical ends
Thready Qty Per Inch (tpi):
24 1st end
Burst Test Pressure:
1250.0 pounds per square inch
Maximum Operating Pressure:
312.0 pounds per square inch
Thread Size:

#### 0.500 inches 1st end

Seat Angle: 12.0 degrees 1st end

### **Hydrostatic Test Pressure:**

625.0 pounds per square inch

#### **Outer Covering Environmental Protection:**

Mildew resistant and salt water resistant

#### **Inside Surface Condition:**

Smooth

# NSN 4720-01-531-4281

**Fiig:** A541y0

Nonmetallic Tubing Assembly - Page 2 of 2



Measuring Method And Length:
48.000 inches
Special Features:
$4720\text{-}01\text{-}095\text{-}2040 \text{ hose}, \ 4730\text{-}00\text{-}139\text{-}3885 \text{ fittings}, \ \text{assembled with markings and marker cable}; \ \text{pneumatical prediction}$
Material:
Plastic polyamide tube
Thread Series Designator:
Uns 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No