NSN 4720-01-531-4508

Cross Sectional Shape:

Convoluted

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-531-4508

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
1.312 inches
Minimum Inside Bending Radius:
3.000 inches
End Application:
C-17a aircraft
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Internal support
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
Outer layer braided polyamide cord
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
1.312 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:

NSN 4720-01-531-4508

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length	Meas	surina	Method	And	Lenath
-----------------------------	------	--------	--------	-----	--------

27.375 inches working

Thread Series Designator:

Unj 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0