NSN 4720-01-533-2871

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-533-2871

Pipe Size Accommodated: 6.000 inches 1st end Cross Sectional Shape: Round Inside Diameter: 6.000 inches Tempurature Rating: 22.0 degrees fahrenheit single response Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter: 0.690 inches 1st end		
Cross Sectional Shape: Round Inside Diameter: 6.000 inches Tempurature Rating: 22.0 degrees fahrenheit single response Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Round Inside Diameter: 6.000 inches Tempurature Rating: 22.0 degrees fahrenheit single response Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Inside Diameter: 6.000 inches Tempurature Rating: 22.0 degrees fahrenheit single response Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Tempurature Rating: 22.0 degrees fahrenheit single response Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Tempurature Rating: 22.0 degrees fahrenheit single response Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
22.0 degrees fahrenheit single response Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Bolt Circle Diameter: 8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
8.880 inches 1st end Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Outside Diameter: 6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
6.880 inches Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Minimum Inside Bending Radius: 42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
42.000 inches Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Bolt Hole Quantity: 12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
12 1st end End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
End Application: Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Miscellaneous parts Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Connection Style: Plain swivel 1st end Bolt Hole Diameter:		
Plain swivel 1st end Bolt Hole Diameter:		
Bolt Hole Diameter:		
0.690 inches 1st end		
0.690 inches 1st end		
End Flange Construction:		
Solid 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Plain face flange 1st end		
Layer Composition And Location:		
1st layer braided synthetic cord and outer layer molded rubber, synthetic		
Maximum Operating Pressure:		
150.0 pounds per square inch		
Flow Angle:		
90.0 degrees 2nd end		
Criticality Code Justification:		
Feat		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
33.000 inches excluding end fittings		

Flange Style:

Round w/ bolt holes 1st end

NSN 4720-01-533-2871

Nonmetallic Hose Assembly - Page 2 of 2



Sp	ecial	Features:

Export control, military critical

Media For Which Designed:

Water single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0