## NSN 4720-01-534-3612

**Cross Sectional Shape:** 

Round

**Thread Class:** 

9.250 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-534-3612

3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.391 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response		
Outside Diameter:		
Between 0.585 inches and 0.615 inches		
Minimum Inside Bending Radius:		
2.880 inches		
Connection Style:		
Swivel nut, flareless 2nd end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Electrostatic discharge capability		
Burst Test Pressure:		
14000.0 pounds per square inch		
Layer Composition And Location:		
Outer layer braided corrosion resistant steel wire		
Maximum Operating Pressure:		
3000.0 pounds per square inch		
Thread Size:		
0.750 inches 2nd end		
Seat Angle:		
12.0 degrees 2nd end		
Hydrostatic Test Pressure:		
6000.0 pounds per square inch		
Flow Angle:		
90.0 degrees 2nd end		
Outer Covering Environmental Protection:		
Ethylene glycol resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		

## NSN 4720-01-534-3612

Nonmetallic Hose Assembly - Page 2 of 2



		_
Thread	l Series	Designator:

Unjf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0