NSN 4720-01-534-6092

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-534-6092

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.355 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
0.750 inches
Exterior Color:
Black
End Application:
C-17a aircraft
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated polyamide fabric
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.563 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Inside Surface Condition:
Convoluted
Measuring Method And Length:
14.500 inches working
Product Name:

Hose assembly, nonmetallic-flared, al, general purpose

NSN 4720-01-534-6092

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0