## NSN 4720-01-535-0882

**Cross Sectional Shape:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-535-0882

Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.620 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.080 inches
Minimum Inside Bending Radius:
6.500 inches
End Application:
Missle gas system
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Nipple copper alloy all ends
Connection Type:
Threaded external tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
2200.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided synthetic cord err-100
Maximum Operating Pressure:
550.0 pounds per square inch
Thread Size:
1.750 inches 1st end
Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth

## NSN 4720-01-535-0882

**Fiig:** A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
25.840 inches
Special Features:
Critical technology; fitting bronze with monel socket; union style with o'ring seal
Media For Which Designed:
Water, fresh single response and water, salt single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No