NSN 4720-01-535-0888

Nonmetallic Hose Assembly - Page 1 of 2



Tremmetame ridge ridge ridge ridge
View Online at https://aerobasegroup.com/nsn/4720-01-535-0888
Pipe Size Accommodated:
2.000 inches 1st end
Cross Sectional Shape:
Round
Inside Diameter:
1.810 inches
Tempurature Rating:
122.0 degrees fahrenheit single response
Outside Diameter:
2.220 inches
Minimum Inside Bending Radius:
13.250 inches
Angle Between Rigid Elbow Fittings In Deg:
360.0
Bolt Hole Quantity:
4 2nd end
End Application:
Missile gas system
Connection Style:
Raised swivel 1st end
Raised Face Height:
0.015 inches 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Flange nickel alloy 400 1st end
Connection Type:
Plain face flange 2nd end
Second End Relationship With First End:

Not identical

Burst Test Pressure:

1400.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

350.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

NSN 4720-01-535-0888

Nonmetallic Hose Assembly - Page 2 of 2



Criticality Code Justification:
Feat
Inside Surface Condition:
Smooth
Measuring Method And Length:
66.000 inches excluding end fittings
Second End Swivel Action Capability:
Not included
Flange Style:
Round w/ bolt holes 2nd end
Special Features:
Critical technology; swivel flange end fittings with 90 degree dogleg elbow 45 inches from straight end, 21 inches from elbow end;
combined length 73.1 inches
Media For Which Designed:
Air single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0