## NSN 4720-01-536-6599

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-536-6599 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.000 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 1.265 inches **Minimum Inside Bending Radius:** 5.500 inches **End Application:** H46 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 3000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire **Maximum Operating Pressure:** 750.0 pounds per square inch **Thread Size:** 1.312 inches 1st end Seat Angle: 37.0 degrees 1st end Flow Angle: 45.0 degrees 2nd end **Outer Covering Environmental Protection:** Abrasion resistant **Inside Surface Condition:** 

**Measuring Method And Length:** 

21.625 inches working

Smooth

## NSN 4720-01-536-6599

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Hose has .109 inch wall thickness
Media For Which Designed:
Gas and fuel/oil, hydrocarbon single response
Thread Series Designator:
Unj 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0