NSN 4720-01-537-4843

Unjf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-537-4843

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.710 inches |
| Minimum Inside Bending Radius: |
| 0.750 inches |
| Angle Between Rigid Elbow Fittings In Deg: |
| 90.0 |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Elbow 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 550.0 pounds per square inch |
| Maximum Operating Pressure: |
| 148.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 285.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 20.000 inches working |
| Product Name: |
| Hose assembly, metallic |
| Thread Series Designator: |

NSN 4720-01-537-4843

Nonmetallic Hose Assembly - Page 2 of 2



| She | lf | Life: | |
|------|----|-------|--|
| Oile | •• | LIIV. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0