Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-538-9942

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-35.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.880 inches
Minimum Inside Bending Radius:
5.000 inches
End Application:
Radar transmitter
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
800.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
33.000 inches working
Special Features:
Item is hose assembly 2904943-49 plus 2903617-53 sleeve. 316 stainless steel; layer composition and location 1st layer braided cotton
cord or braided rayon cord outer cover molded rubber, ethylenepropylene dienne-poly=methylene
Thread Series Designator

Thread Series Designator:

Unjf 1st end

NSN 4720-01-538-9942

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

