NSN 4720-01-539-3136

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-539-3136

Cross Sectional Shape:
Round
Thread Class:
18 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.313 inches

Tempurature Rating:

-58.0 degrees fahrenheit single response and 302.0 degrees fahrenheit single response

Outside Diameter:

0.620 inches

Minimum Inside Bending Radius:

1.000 inches

Exterior Color:

Black

End Application:

TRUC-K,-TRA-CTOR

Connection Style:

Flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal hose 2nd end

Burst Test Pressure:

2000.0 pounds per square inch

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.560 inches 2nd end

Seat Angle:

45.0 degrees 2nd end

Flow Angle:

45.0 degrees 2nd end

Measuring Method And Length:

43.000 inches

Product Name:

Hose assembly num 6 cr 43.0 2944

Special Features:

Engine and brake hose; synthetic rubber tube; one braid of fiber reinforcement; an entangled filament black nylon fiber outer braid that is oil,

weather, and abrasion resistant

Thread Series Designator:

Unc 2nd end

NSN 4720-01-539-3136

Metallic Hose Assembly - Page 2 of 2



Specification Data:

81343 - j1402ai professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0