NSN 4720-01-539-3136

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-539-3136

view Offilite at https://defobasegroup.com/hist//4720-01-333-3130
Cross Sectional Shape:
Round
Thread Class:
18 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-58.0 degrees fahrenheit single response and 302.0 degrees fahrenheit single response
Outside Diameter:
0.620 inches
Minimum Inside Bending Radius:
1.000 inches
Exterior Color:
Black
End Application:
TRUC-K,-TRA-CTOR
Connection Style:
Flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 2nd end
Burst Test Pressure:
2000.0 pounds per square inch
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.560 inches 2nd end
Seat Angle:
45.0 degrees 2nd end
Flow Angle:
45.0 degrees 2nd end
Measuring Method And Length:
43.000 inches
Product Name:
Hose assembly num 6 cr 43.0 2944
Special Features:
Engine and brake hose; synthetic rubber tube; one braid of fiber reinforcement; an entangled filament black nylon fiber outer braid that is oil
weather, and abrasion resistant
Thread Series Designator:

Unc 2nd end

NSN 4720-01-539-3136

Metallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

81343 - j1402ai professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0