Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-539-4595

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| Between 0.375 inches and 0.398 inches |
| Tempurature Rating: |
| -40.0 degrees celsius single response and 100.0 degrees celsius single response |
| Outside Diameter: |
| 0.777 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| End Application: |
| ENDI-TE-MNS-N:54 |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal hose 1st end |
| Thready Qty Per Inch (tpi): |
| 16 1st end |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 4000.0 pounds per square inch |
| Thread Size: |
| 0.687 inches 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 67.000 inches working |
| Special Features: |
| Fittings are made of type 304 corrosion resistant steel. |
| Media For Which Designed: |
| Hydraulic fluid single response and hydraulic fluid, water base single response |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |
| N/a |
| |

NSN 4720-01-539-4595

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0