Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-539-4765

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: Between 0.750 inches and 0.781 inches Tempurature Rating: -40.0 degrees celsius single response and 121.0 degrees celsius single response Outside Diameter: 1.120 inches Minimum Inside Bending Radius: 9.500 inches
Thread Class:2b 1st endThread Direction:Right-hand 1st endInside Diameter:Between 0.750 inches and 0.781 inchesTempurature Rating:-40.0 degrees celsius single response and 121.0 degrees celsius single responseOutside Diameter:1.120 inchesMinimum Inside Bending Radius:9.500 inches
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: Between 0.750 inches and 0.781 inches Tempurature Rating: -40.0 degrees celsius single response and 121.0 degrees celsius single response Outside Diameter: 1.120 inches Minimum Inside Bending Radius: 9.500 inches
Thread Direction:Right-hand 1st endInside Diameter:Between 0.750 inches and 0.781 inchesTempurature Rating:-40.0 degrees celsius single response and 121.0 degrees celsius single responseOutside Diameter:1.120 inchesMinimum Inside Bending Radius:9.500 inches
Right-hand 1st endInside Diameter:Between 0.750 inches and 0.781 inchesTempurature Rating:-40.0 degrees celsius single response and 121.0 degrees celsius single responseOutside Diameter:1.120 inchesMinimum Inside Bending Radius:9.500 inches
Inside Diameter: Between 0.750 inches and 0.781 inches Tempurature Rating: -40.0 degrees celsius single response and 121.0 degrees celsius single response Outside Diameter: 1.120 inches Minimum Inside Bending Radius: 9.500 inches
Between 0.750 inches and 0.781 inches Tempurature Rating: -40.0 degrees celsius single response and 121.0 degrees celsius single response Outside Diameter: 1.120 inches Minimum Inside Bending Radius: 9.500 inches
Tempurature Rating: -40.0 degrees celsius single response and 121.0 degrees celsius single response Outside Diameter: 1.120 inches Minimum Inside Bending Radius: 9.500 inches
-40.0 degrees celsius single response and 121.0 degrees celsius single response Outside Diameter: 1.120 inches Minimum Inside Bending Radius: 9.500 inches
Outside Diameter: 1.120 inches Minimum Inside Bending Radius: 9.500 inches
1.120 inches Minimum Inside Bending Radius: 9.500 inches
Minimum Inside Bending Radius: 9.500 inches
9.500 inches
End Application:
ENDI-TE-MNS-N:54
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Maximum Operating Pressure:
27.6 pounds per square inch
Thread Size:
1.187 inches 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
141.000 inches working and 142.000 inches working
Special Features:
Fittings are made of type 304 corrosion resistant steel.
Media For Which Designed:
Hydraulic fluid single response and hydraulic fluid, water base single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0