

View Online at <https://aerobasegroup.com/nsn/4720-01-540-1279>

**Pipe Size Accommodated:**

1.500 inches 1st end

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.810 inches

**Outside Diameter:**

2.220 inches

**Minimum Inside Bending Radius:**

13.250 inches

**Hose Or Tubing Specification/std Data:**

Mil-h-24136/3 size 32 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**End Application:**

Ssgn fire fighting system

**Connection Style:**

External seat for gasket seal (boss) 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

1400.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer spirally wrapped steel fabric err-100

**Maximum Operating Pressure:**

350.0 pounds per square inch

**Thread Size:**

3.062 inches 1st end

**Criticality Code Justification:**

Feat

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

48.100 inches working

**Special Features:**

Military critical, export control; 2 inch hose with 1.5 nps oring sealed union connections; label required

**Media For Which Designed:**

Water single response

**Thread Series Designator:**

Un 1st end

**Specification Data:**

Mil-h-24136/3 size 32 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0

**Mil-std (military Standard):**

Mil-h-24136 spec.