NSN 4720-01-540-1542

Nonmetallic Hose Assembly - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/4720-01-540-1542
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
200.0 degrees fahrenheit single response
Outside Diameter:
0.781 inches
End Application:
2330-01-508-7887, trailer, flat bed
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18.0 1st end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and outer layer molded rubber, synthetic
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
45.0 degrees 2nd end
Hydrostatic Test Pressure:
300.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
1016.0 millimeters

Media For Which Designed:

Air single response

NSN 4720-01-540-1542

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Sorios	Designator	
ımread	i Series	Designator	

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0