NSN 4720-01-540-3959

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-540-3959

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
20 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
22.000 inches working
Product Name:
Hose assembly, ptfe, cres reinforced, 3000 psi, 400 degrees f, straight to straight, flared, lightweight
Thread Series Designator:
Unjf 1st end

NSN 4720-01-540-3959

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifi	cation	Data
------	-----	--------	------

81343-as115 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0