

View Online at <https://aerobasegroup.com/nsn/4720-01-540-3966>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.391 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

1.500 inches

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

12.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

50.000 inches working

Product Name:

Hose assembly, ptfе, cres reinforced, 3000 psi, 400 degrees f, straight to straight, flared, lightweight

Thread Series Designator:

Unjf 1st end

Specification Data:

81343-as115 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0