## NSN 4720-01-540-3972

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-540-3972

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outside Diame	ster.
0.250 inches	
Minimum Insid	le Bending Radius:
1.500 inches	
Connection St	yle:
Swivel nut, flar	eless 1st end
End Connection	on Design:
Straight 1st end	I
Connection Ty	ре:
Threaded intern	nal tube 1st end
Thready Qty P	er Inch (tpi):
20 1st end	
<b>Burst Test Pre</b>	ssure:
16000.0 pounds	s per square inch
Layer Compos	ition And Location:
Outer layer brai	ided corrosion resistant steel wire
Maximum Ope	rating Pressure:
3000.0 pounds	per square inch
Thread Size:	
0.438 inches 1s	st end
Seat Angle:	
12.0 degrees 1s	st end
Hydrostatic Te	est Pressure:
6000.0 pounds	per square inch
Inside Surface	Condition:
Smooth	
Measuring Met	thod And Length:
72.000 inches	working
Product Name	:
Hose assembly	, ptfe, cres reinforced, 3000 psi, 400 degrees f, straight to straight, flared, lightweight
Thread Series	Designator:
Unjf 1st end	

## NSN 4720-01-540-3972

Nonmetallic Hose Assembly - Page 2 of 2



Spec	cific	ation	Data:
------	-------	-------	-------

81343-as115 professional/industrial association specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0