NSN 4720-01-540-3975

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches

Tempurature Rating:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-540-3975

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

Outsi	ide Diameter:
0.500	inches
Minin	num Inside Bending Radius:
1.500	inches
Conn	nection Style:
Swive	el nut, flareless 1st end
End (Connection Design:
Straig	ght 1st end
Conn	nection Type:
Threa	aded internal tube 1st end
Threa	ady Qty Per Inch (tpi):
20 1s	t end
Burst	t Test Pressure:
16000	0.0 pounds per square inch
Laye	r Composition And Location:
Outer	layer braided corrosion resistant steel wire
Maxir	mum Operating Pressure:
3000.	0 pounds per square inch
Threa	ad Size:
0.438	sinches 1st end
Seat	Angle:
12.0	degrees 1st end
Hydro	ostatic Test Pressure:
6000.	0 pounds per square inch
Inside	e Surface Condition:
Smoo	oth
Meas	suring Method And Length:
36.00	0 inches working
Produ	uct Name:
Hose	assembly, ptfe, cres reinforced, 3000 psi, 400 degrees f, straight to straight, flared, lightweight
Threa	ad Series Designator:
Unif 1	st end

NSN 4720-01-540-3975

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81343-as115 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0