## NSN 4720-01-540-8354

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-540-8354 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.313 inches **Minimum Inside Bending Radius:** 2.000 inches **End Application:** Ecp g-566 **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant and oil resistant and fuel resistant and hydraulic solution resistant and alcohol resistant **Vacuum In Torr:** 50.8 **Inside Surface Condition:** Smooth

**Measuring Method And Length:** 68.000 inches working

## NSN 4720-01-540-8354

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Burst 7000psi at 450 degree f

Thread Series Designator:

Unjf 1st end

**Specification Data:** 

96906-ms8005 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0