NSN 4720-01-543-2847

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-543-2847 **Cross Sectional Shape:** Round **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 1.810 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 2.200 inches **Minimum Inside Bending Radius:** 13.250 inches **End Application:** Ship; ssgn fire fighting system **Connection Style:** External seat for gasket seal (boss) 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external boss 1st end Thready Qty Per Inch (tpi): 12 1st end **Burst Test Pressure:** 1400.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided polyester cord and 2nd layer braided polyester cord **Maximum Operating Pressure:** 350.0 pounds per square inch **Thread Size:** 3.062 inches 1st end **Hydrostatic Test Pressure:** 700.0 pounds per square inch **Criticality Code Justification:** Feat **Inside Surface Condition:** Smooth **Measuring Method And Length:**

48.100 inches

Special Features:

Weapon system essential, export control; union thread connections

NSN 4720-01-543-2847

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ned:
--	-------	-----	-------	--------	------

Air and fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A542a0