NSN 4720-01-544-6078

Cross Sectional Shape:

Round

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-544-6078

| 2b 1st end |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.375 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| End Application: |
| Force system, refueler |
| Connection Style: |
| Nut assembly with gasket 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal hose 1st end |
| Burst Test Pressure: |
| 6500.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.500 inches 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 37.000 inches |
| Product Name: |
| Assembly, hose fuel piping (static dissipating) |
| Special Features: |
| Location: eductor to fuel tank |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| |

NSN 4720-01-544-6078

Nonmetallic Hose Assembly - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

--

Demilitarization:

No

Fiig:

A542a0