Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-544-7255

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.500 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response  |
| Outside Diameter:  |
| 0.656 inches   |
| Minimum Inside Bending Radius:   |
| 5.500 inches   |
| End Application:   |
| Force system, refueler   |
| Connection Style:  |
| Flare 1st end  |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 5500.0 pounds per square inch  |
| Layer Composition And Location:  |
| Outer layer braided corrosion resistant steel wire   |
| Maximum Operating Pressure:  |
| 1500.0 pounds per square inch  |
| Thread Size:   |
| 0.875 inches 1st end   |
| Seat Angle:  |
| 37.0 degrees 1st end   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 41.500 inches  |
| Product Name:  |
| Assembly, hose fuel piping ((static dissipating)   |
| Special Features:  |
| Location of hose assembly: pump inlet to tee under air eliminator; hose has stainless steel, female jic fittings on both ends. |
| Thread Series Designator:  |
| Unf 1st end  |
|  |

## NSN 4720-01-544-7255

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

