Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-545-3006

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.880 inches
Minimum Inside Bending Radius:
7.000 inches
End Application:
Light amphibious recovery craft
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
17000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire
Maximum Operating Pressure:
4250.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees and 45.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
64.000 inches working
Product Name:
Inavy: hose assembly 64in
Media For Which Designed:
Air and hydraulic fluid and oil, lubricating, diester base and water single response
Thread Series Designator:
Unf 1st end

## NSN 4720-01-545-3006

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

