NSN 4720-01-545-5087

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-545-5087 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.500 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.880 inches **Minimum Inside Bending Radius:** 7.000 inches **End Application:** Light amphibious resupply craft (larc v) **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 17000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire **Maximum Operating Pressure:** 4250.0 pounds per square inch Thread Size: 0.750 inches 2nd end Seat Angle: 37.0 degrees and 45.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:**

66.000 inches

Product Name:

(inavy) hose assembly, 66 in.

Media For Which Designed:

Air and fuel/oil, hydrocarbon and water single response

NSN 4720-01-545-5087

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0