## NSN 4720-01-545-5123

Air and hydraulic fluid and water single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-545-5123

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
2.150 inches
Minimum Inside Bending Radius:
20.000 inches
End Application:
Light amphibious resupply craft (larc v)
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
7200.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire
Maximum Operating Pressure:
1800.0 pounds per square inch
Thread Size:
1.875 inches 1st end
Seat Angle:
37.0 degrees and 45.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.000 inches
Product Name:
(inavy)hose assembly, 42 in
Media For Which Designed:

## NSN 4720-01-545-5123

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Shelf Life:
N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0