Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-545-5588

Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut fare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 0.562 inches 1st end Straight 1st end Conception State 1st end Straight 1st end Connection Type: Threaded internal tube 1st end 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 0.562 inches 1st end Straight 1st end Conception State 1st end Straight 1st end Conception State 1st end Straight 1st end Connection Type: Thread Size: 0.562 inches 1st end Straight 1st end Conception State 1st end Concepti
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: 40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.3750 inches Minimun Inside Bending Radius: 5.000 inches End Application: Light maphibious recovery craft Connection Dsign: Straight 1st end Percomposition And Location: Straight 1st end Connection Dsign: Straight 1st end Durer source square inch Layer Composition And Location: Durer wolded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressue: Strolo, op ounds per square inch Hereed Stree: 0.562 inches 1st end Stree: Strolo op ounds per square inch Hereed Stree: 0.562 inches 1st end Stree: 0.562 inches 1st end Stree: Strologerees and 45.0 degrees 1st end Stree:<
Sub Tale and Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Strigt 1 st end Connection Dusign: Stragt 1 st end Burst Test Pressure: 20000.0 pounds per square inch Burst Test Pressure: 20000.0 pounds per square inch Aximum Operating Pressure: 5000.0 pounds per square inch Straige: 0x00.0 pounds per square inch Straige: 0x00.0 pounds per square inch Straige: 0x1.0 degrees and 45.0 degrees 1st end Straige: 0x1.0 degrees and 45.0 degrees 1st end Hales Surface Condition: Strouge: 0x1.0 degrees and 45.0 degrees 1st end
Thread Direction: Right-hand 1st end Inside Diameter: 0.375 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimum Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Design: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: Stroon, pounds per square inch Maximum Operating Pressure: Stroon, pounds per square inch Stread Stree Stroon, pounds per square inch Thread Size: 0.502 inches 1st end Straight St end Stread Angle: 37.0 degrees and 45.0 degrees 1st end </td
Right-hand ist end Inside Diameter: 0.375 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Dslgi: Swivel nut flare 1st end End Connection Design: Straight 1st end Duroted nuture 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: 0x000.0 pounds per square inch Stringen Sist end Stringen Sist end </td
Inside Diameter: 0.375 inches Tempurature Rating: -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Durst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Oxolop opunds per square inch Miximum Operating Pressure: 9000.0 pounds per square inch Straiget 10.622 inches 1st end Straigen moleed rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire 9000.0 pounds per square inch Marium Operating Pressure: 90.622 inches 1st end 9.622 inches 1st end 9.622 inches 1st end 9.704 express and 45.0 degrees 1st end 9.704 method And Length: 9.000 inches
0.375 inchesTempurature Rating:-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single responseOutside Diameter:0.750 inchesMinimun Inside Bending Radius:5.000 inchesEnd Application:Light amphibious recovery craftConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endDometion Type:Threade internal tube 1st endBurst Test Pressure:20000.0 pounds per square inchLayer composition And Location:Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire5.622 inches 1st endBurst Test Pressure:0.002.0 pounds per square inchLayer Composition And Location:0.002.1 pounds per square inchStried Steel0.562 inches 1st endBurst Test Pressure:0.562 inches 1st endBurst Test Pressure:1.562 inches 1st endBurst Test Pressure:1.562 inches 1st endBurst Test Pressure:1.562 inches 1st endBurst Test Pressure:1.
Tempurature Rating: 40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Statagel: 17.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Donnection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Chread Size: 0.562 inches 1st end Burst Test Pressure: 5000.0 pounds per square inch Chread Size: 0.562 inches 1st end Straight 1st end Burst Test Pressure: 5000.0 pounds per square inch Hareed Haring Method And Length Jodegrees and 45.0 degrees 1st end Haring Method And Length: J0.000 inches Product Name:
Outside Diameter: 0.750 inches Minimun Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 2000.0 pounds per square inch Thread Size: 0.562 inches 1st end Straight 1st end Straight 2st end Straight 2st end Connection Type: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 500.0 pounds per square inch Thread Size: 0.562 inches 1st end Straight 2st flage 10.61 egrees and 45.0 degrees 1st end Inside Surface Condition: Smoth Measuring
0.750 inches Minimur Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Steat Angle: 37.0 degrees and 45.0 degrees 1st end Maximus Mathematica Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
Minimum Inside Bending Radius: 5.000 inches End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Date and Size: 0.562 Inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smoth Measuring Method And Length: 19.000 inches Product Name:
5.000 inchesEnd Application:Light amphibious recovery craftConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:20000.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire5000.0 pounds per square inchStried Size:3000.0 pounds per square inchStried Size:30.562 inches 1st endSeat Angle:37.0 degrees and 45.0 degrees 1st endInside Surface Condition:SnothMeasuring Method And Length:19.000 inchesProduct Name:
End Application: Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Smooth Measuring Method And Length: 19.000 inches Product Name:
Light amphibious recovery craft Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Cuter layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire 7000.0 pounds per square inch Sustername Operating Pressure: 5000.0 pounds per square inch Furead Size: 0.562 inches 1st end Sougrees and 45.0 degrees 1st end Sustername Condition: Snooth Maximum Method And Length: 19.000 inches
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Hasuring Method And Length: 19.000 inches Product Name:
Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:20000.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire5000.0 pounds per square inchMaximum Operating Pressure:5000.0 pounds per square inchFuread Size:0.562 inches 1st endSeat Angle:37.0 degrees and 45.0 degrees 1st endInside Surface Condition:SmoothMexaring Method And Length:19.000 inchesProduct Name:
End Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endBurst Test Pressure:20000.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire5000.0 pounds per square inchMaximum Operating Pressure:5000.0 pounds per square inchStread Size:0.562 inches 1st endSeat Angle:37.0 degrees and 45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:19.000 inchesProduct Name:
Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches
Connection Type:Threaded internal tube 1st endBurst Test Pressure:20000.0 pounds per square inchLayer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wireMaximum Operating Pressure:5000.0 pounds per square inchThread Size:0.562 inches 1st endSeat Angle:37.0 degrees and 45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:19.000 inchesProduct Name:
Threaded internal tube 1st end Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
Burst Test Pressure: 20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
20000.0 pounds per square inch Layer Composition And Location: Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch 5000.0 pounds per square inch 1.562 inches 1st end 5.624 Angle: 37.0 degrees and 45.0 degrees 1st end 5.700 degrees 1st
Layer Composition And Location:Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wireMaximum Operating Pressure:5000.0 pounds per square inchThread Size:0.562 inches 1st endSeat Angle:37.0 degrees and 45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:19.000 inchesProduct Name:
Outer layer molded rubber, synthetic and 1st layer braided steel wire and 2nd layer braided steel wire Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
Maximum Operating Pressure:5000.0 pounds per square inchFhread Size:0.562 inches 1st endSeat Angle:37.0 degrees and 45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:19.000 inchesProduct Name:
5000.0 pounds per square inch Thread Size: 0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
Thread Size:0.562 inches 1st endSeat Angle:37.0 degrees and 45.0 degrees 1st endInside Surface Condition:SmoothMeasuring Method And Length:19.000 inchesProduct Name:
0.562 inches 1st end Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
Seat Angle: 37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
37.0 degrees and 45.0 degrees 1st end Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
Inside Surface Condition: Smooth Measuring Method And Length: 19.000 inches Product Name:
Smooth Measuring Method And Length: 19.000 inches Product Name:
Measuring Method And Length: 19.000 inches Product Name:
19.000 inches Product Name:
Product Name:
(inavy) hose assembly 19 in
Media For Which Designed:
Air and hydraulic fluid and oil, lubricating, diester base and water single response
Thread Series Designator:
Unf 1st end

NSN 4720-01-545-5588

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

