NSN 4720-01-545-6367

Media For Which Designed:

Hydraulic fluid and oil, lubricating, diester base and water single response

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-545-6367

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.880 inches
Minimum Inside Bending Radius:
7.000 inches
End Application:
Light amphibious resupply craft (larc-v)
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
17000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer wrapped rubber, synthetic and 3rd layer braided steel wire and outer layer molded rubber,
synthetic
Maximum Operating Pressure:
4250.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees and 45.0 degrees 1st end
Flow Angle:
45.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
45.000 inches
Product Name:
(inavy) hose assembly, 45 in

NSN 4720-01-545-6367

Nonmetallic Hose Assembly - Page 2 of 2



Thread S	Series	Designator:
----------	--------	-------------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0