## NSN 4720-01-545-7024

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-545-7024

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.250 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit single response and 257.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 1.970 inches  |
| Minimum Inside Bending Radius:  |
| 17.500 inches   |
| End Application:  |
| Light amphibious resupply craft (larc v)  |
| Connection Style:   |
| Gasket seal 1st end   |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Thready Qty Per Inch (tpi):   |
| 12 1st end  |
| Burst Test Pressure:  |
| 24000.0 pounds per square inch  |
| Maximum Operating Pressure:   |
| 6000.0 pounds per square inch   |
| Thread Size:  |
| 1.688 inches 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 70.000 inches   |
| Product Name:   |
| (inavy) hose assembly, 70in   |
| Thread Series Designator:   |
| Un 1st end  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 4720-01-545-7024

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0