NSN 4720-01-547-3939

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-547-3939

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Angle Between Rigid Elbow Fittings In Deg:
270.0
End Application:
U-2 aircraft
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Vacuum In Torr:
50.8

NSN 4720-01-547-3939

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:
Smooth
Measuring Method And Length:
9.500 inches working
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8006 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

Fiig: A542a0