NSN 4720-01-547-9759

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-547-9759

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.630 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response
Outside Diameter:
1.080 inches
Minimum Inside Bending Radius:
2.750 inches
Exterior Color:
Blue
End Application:
Pwp mod 1 cmu assembly
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Fire resistant

Smooth

Measuring Method And Length:

Inside Surface Condition:

44.880 inches excluding end fittings

NSN 4720-01-547-9759

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Modified nsn 4720-01-538-2800 with the difference being rev c on drawing having a hose label

Media For Which Designed:

Water single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0