NSN 4720-01-548-6841



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-01-548-6841 **Cross Sectional Shape:** Round **Inside Diameter:** 0.250 inches **Tempurature Rating:** 185.0 degrees fahrenheit single response **Outside Diameter:** 0.560 inches **Minimum Inside Bending Radius:** 3.000 inches **Quick Disconnect Size:** 0.250 inches 2nd end **End Application:** Station, cleaning bench **Connection Style:** Push (internal) 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Internal quick disconnect 2nd end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided textile yarn and 2nd layer braided textile yarn **Maximum Operating Pressure:** 1250.0 pounds per square inch **Criticality Code Justification:** Feat **Inside Surface Condition:** Smooth **Measuring Method And Length:** 5.000 feet excluding end fittings **Special Features:** Military critical, export control; steel quick disconnect Media For Which Designed:

Water single response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 4720-01-548-6841

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0