

View Online at <https://aerobasegroup.com/nsn/4720-01-549-3574>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.656 inches

Minimum Inside Bending Radius:

2.000 inches

Angle Between Rigid Elbow Fittings In Deg:

90.0

End Application:

Aircraft, sh60

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

44.000 inches working

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0