Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-549-4191

Cro	ss Sectional Shape:
Rou	Ind
Thr	ead Direction:
Rigi	ht-hand all ends
Insi	de Diameter:
0.31	13 inches
Ten	npurature Rating:
-22.	0 degrees fahrenheit and 257.0 degrees fahrenheit 1st response
Out	side Diameter:
0.62	20 inches
Min	imum Inside Bending Radius:
1.50	00 inches
End	Application:
232	0-01-529-2251; mrap buffalo mk2a2
Cor	nnection Style:
Swi	vel nut with compression sleeve all ends
Cor	nnection Type:
Thre	eaded internal hose all ends
Max	kimum Operating Pressure:
500	.0 pounds per square inch
Thr	ead Size:
0.75	50 inches all ends
Меа	asuring Method And Length:
15.2	250 inches
Insi	de Diameter Hose Accommodated:
0.62	25 inches all ends
Pro	duct Name:
Ass	y. Compl rear ac high press exp line 1
Spe	ecial Features:
This	s is made with synthetic rubber with nylon barrier, reinforcement one fiber
Med	dia For Which Designed:
Ref	rigerant 22 single response
Thr	ead Series Designator:
Unf	all ends
She	elf Life:
N/a	
Uni	t Of Measure:
Den	nilitarization:
No	
Fiig	:
-	12a0

braid; cover synthetic rubber