NSN 4720-01-550-2968

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-550-2968

| Cross Sectional Shape: |
|---|
| Round |
| Inside Diameter: |
| 1.375 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.750 inches |
| Minimum Inside Bending Radius: |
| 7.500 inches |
| End Application: |
| Kc-135 aircraft |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Elbow 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 360.0 pounds per square inch |
| Maximum Operating Pressure: |
| 120.0 pounds per square inch |
| Seat Angle: |
| 37.0 degrees 1st end |
| Flow Angle: |
| 90.0 degrees 1st end |
| Inside Surface Condition: |
| Convoluted |
| Measuring Method And Length: |
| 17.000 inches |
| Product Name: |
| Hose assembly, manual defueling valve |
| Special Features: |
| Flange p/n is ms20756-j32 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |