NSN 4720-01-551-5929

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-551-5929

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.359 inches and 0.391 inches
Tempurature Rating:
-67.0 degrees fahrenheit single response and 158.0 degrees fahrenheit single response
Outside Diameter:
Between 0.453 inches and 0.500 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
Outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
150.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and fuel resistant and light resistant and oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
7.135 inches working and 7.375 inches working
Media For Which Designed:
Air single response
Thread Series Designator:
Unjf 1st end

NSN 4720-01-551-5929

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0