Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-553-3460

| Cross Sectional Shape: | |
|---|--|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Inside Diameter: | |
| 0.500 inches | |
| Tempurature Rating: | |
| -65.0 degrees fahrenheit single response and 160.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.700 inches | |
| Minimum Inside Bending Radius: | |
| 1.000 inches | |
| End Application: | |
| 7380001-03, ecs so1 bay | |
| End Connection Design: | |
| Straight 2nd end | |
| Thready Qty Per Inch (tpi): | |
| 18 1st end | |
| Burst Test Pressure: | |
| 820.0 pounds per square inch | |
| Maximum Operating Pressure: | |
| 148.0 pounds per square inch | |
| Thread Size: | |
| 0.750 inches 2nd end | |
| Hydrostatic Test Pressure: | |
| 410.0 pounds per square inch | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 36.500 inches working | |
| Outside Diameter Tube Accommodated: | |
| 0.500 inches 2nd end | |
| Product Name: | |
| Hose assembly | |
| Thread Series Designator: | |
| Unjf 1st end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 4720-01-553-3460

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

