Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-554-9726

Cross Se	ctional Shape:
Round	
Thread C	lass:
2b 1st end	d
Thread D	irection:
Right-han	d 1st end
Inside Dia	ameter:
0.500 incł	nes
Tempura	ture Rating:
-65.0 deg	rees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside I	Diameter:
0.615 incł	nes
Minimum	Inside Bending Radius:
2.875 incł	nes
End Appl	lication:
Asds; ope	er compt piping install
Connecti	on Style:
Gasket se	eal / optional end 2nd end
End Con	nection Design:
Straight 1	st end
Connecti	on Type:
Threaded	internal boss 2nd end
Burst Tes	st Pressure:
12000.0 p	oounds per square inch
Maximun	n Operating Pressure:
5000.0 pc	ounds per square inch
Thread S	ize:
0.812 incl	nes 1st end
Flow Ang	jle:
0	ees 2nd end
Inside Su	Irface Condition:
Smooth	
Measurin	g Method And Length:
31.625 ind	ches working
Thread S	eries Designator:
Unf 2nd e	
Shelf Life	
N/a	
Unit Of M	leasure:
Demilitar	ization:
No	

NSN 4720-01-554-9726

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

