Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-555-1306

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.892 inches
Minimum Inside Bending Radius:
4.000 inches
End Application:
Lio/tc piping
Connection Style:
Gasket seal / optional end 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
16 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded plastic and 1st layer braided fiber and 2nd layer braided fiber
Maximum Operating Pressure:
3500.0 pounds per square inch
Thread Size:
0.812 inches 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.250 inches working
Product Name:
Flex hose acl-fh-84



Special Features:

Inner tube nylon with internal support; nuts have lockwire holes; threads mate with h849t-8

Media For Which Designed:

Refrigerant 13 single response

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0