

View Online at <https://aerobasegroup.com/nsn/4720-01-555-3051>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

1.138 inches

Minimum Inside Bending Radius:

6.500 inches

End Application:

Lio/tc piping

Connection Style:

Gasket seal / optional end 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal boss 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded plastic and 1st layer braided fiber and 2nd layer braided fiber

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

1.250 inches 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

56.000 inches working

Product Name:

Flex hose lcl-fh-82

Special Features:

Fitting material 316l stainless steel; nuts have lockwire holes; threads mate with cpv h849t-12

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0