NSN 4720-01-555-3051

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-555-3051

Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
1.138 inches
Minimum Inside Bending Radius:
6.500 inches
End Application:
Lio/tc piping
Connection Style:
Gasket seal / optional end 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal boss 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded plastic and 1st layer braided fiber and 2nd layer braided fiber
Maximum Operating Pressure:
2250.0 pounds per square inch
Thread Size:
1.250 inches 1st end
Hydrostatic Test Pressure:
4500.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
56.000 inches working
Product Name:
Flex hose Icl-fh-82
Special Features:
Fitting material 316l stainless steel; nuts have lockwire holes; threads mate with cpv h849t-12
Thread Series Designator:
-

NSN 4720-01-555-3051

Nonmetallic Hose Assembly - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0