

View Online at <https://aerobasegroup.com/nsn/4720-01-555-4013>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.617 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

**Outside Diameter:**

0.990 inches

**Minimum Inside Bending Radius:**

3.875 inches

**End Application:**

Lio/tc piping

**Connection Style:**

Gasket seal / optional end 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal boss 1st end

**Burst Test Pressure:**

12000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer molded plastic

**Maximum Operating Pressure:**

5000.0 pounds per square inch

**Thread Size:**

1.250 inches 1st end

**Hydrostatic Test Pressure:**

6000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

31.500 inches working

**Product Name:**

Flex hose lcl-fh-95

**Special Features:**

Polytetrafluoroethylene hose; fittings 316l stainless steel; nuts have lockwire holes; threads mate to cpv h849t-12

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0