

View Online at <https://aerobasegroup.com/nsn/4720-01-555-6973>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

28.4 degrees fahrenheit single response and 95.0 degrees fahrenheit single response

Outside Diameter:

1.060 inches

Minimum Inside Bending Radius:

3.100 inches

End Application:

Lio/tc piping

Connection Style:

Gasket seal / optional end 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal boss 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

4400.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire err-100

Maximum Operating Pressure:

1100.0 pounds per square inch

Thread Size:

1.250 inches 1st end

Hydrostatic Test Pressure:

2200.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

29.750 inches working

Product Name:

Flex hose lcl-fh-32

Special Features:

Hose has internal support, nuts have lockwire holes, mates to cpv h849t-12

Media For Which Designed:

Refrigerant 13 single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0